

OKFLNIMBUS*50

LAMP TYPE Econolight™ Nimbus 50W LED Flood

APPLICATION Floodlighting and security

WORK HEIGHT Up to 6m

WORK ANGLE 120° with optional 75*100° lens







EFFICACY	125 lm/W (fixture)
VOLTAGE	220 V
COLOUR	Black
DIMENSIONS	280x269x74mm
WEIGHT	3,1kg
DRIVER	Sosen
MATERIAL	Aluminium Alloy + Tempered Glass
CERTIFICATION	IEC, RoHS, CE, SAA

Tel: 021 674 1041

Fax: 021 674 1051

The Econolight™ Nimbus high-powered LED floodlight range is perfectly designed to offer efficient lighting solutions over conventional HID lamps. The floodlights are premium - designed with superior LED chip technology and top-of-the-range drivers to ensure longevity and optimally driven currents in comparison to traditional "generic" LED floodlights. The versatility of these lamps is highlighted with the optional lenses offering 75*100 degree beam angle - improving distance and spotlighting requirements.

PACKAGING: Cardboard box

INSTALLING: Direct connection to 220V power

WARRANTY: 5 year manufacturing warranties available - incorrect operation, misuse or unqualified

installation could result in the warranty being voided. Please contact Lighting

Revolution for further explanation on these guidelines.

PRICE: Please contact Lighting Revolution for an official quotation.