

SCDXG02*250


LAMP TYPE 250W Low Frequency External Induction **APPLICATION** High Bay Lamp, Warehousing, Production

WORK HEIGHT 6 ~ 12m

WORK ANGLE 73°







Tel: 021 674 1041

Fax: 021 674 1051

LAMP POWER	250W	
LUMENS	20 000 lm	
ILLUMINATION RANGE	6 m	TBC
	8 m	TBC
	10 m	TBC
LIFESPAN	60 000 h	
COL TEMPS	Warm / Neutral / Cool White	
CRI	> 80	
POWER FACTOR	> 0.95	

VOLTAGE	AC 180 ~ 250 V	
WORK TEMP	-20°C to 50°C	
DIMENSIONS	520 x 506mm mm	
WEIGHT	3.6 kg	
IP RATING	IP20	
PROTECTION	Tempered Glass	
MATERIAL	High-density die-cast Aluminium Alloy	
CERTIFICATION	SABS, CE, RoHS	

The DXG200 High Bay induction lamp offers a wide angle solution perfect for harnessing overlapping light. Used correctly in an array, the beam spread will allow excellent light distribution from a variety of heights according to safety and production requirements. The external induction system is a long life-sapn system for minimising maintenance and low depreciation rates. This makes it an ideal lamp at 8m for production floors, warehouses an open space applications.

PACKAGING: Cardboard box, polystyrene protected.

INSTALLING: Direct connection to 220V power, plug-in induction bulb.

WARRANTY: 3-year manufacturing warranty - incorrect operation, misuse or unqualified

installation could result in the warranty being voided. Please contact Lighting

Revolution for further explanation on these guidelines.

PRICE: Please contact Lighting Revolution for an official quotation.